

Product range

iSOLde – The successful tanning lamp program for all, who appreciate proven product quality.



A perfect team.

iSOLde

Professional tanning lamps



Tanning with pleasure

The intelligent iSOLde product line is the result of years of research of medical institutes in collaboration with Philips. The presented selection of UV lamps was specifically designed for the different skin types and applications. Scientific knowledge about the health effects of UV radiation on humans formed the basis for the development of this tanning lamp program. Mature technologies, advanced materials and reliable quality controls ensure trust and security in the application.

BodyTone by iSOLde

The **BodyTone by iSOLde** low pressure range provides suitable 0,3 lamps for all popular device. According to EU directive the photo biological irradiance value is limited to 0.3 W/m². New or used equipment can be converted immediately to comply with 0.3 through BodyTone by iSOLde. How? Just compare the UV code on the lamp with the equivalence scope stipulated in the passport of the device. If wattage and reflector type are matching and X-/Y-values are within the scope the lamps may be used.

BodyTone characteristics

- Tanning:
 - Naturally and gentle on skin
 - Enjoyment without compromise
- Qualities of well-being for your skin:
 - Little to no redness
 - No skin irritation
 - Less odour after tanning



XPT lamps

iSOLde lamps equipped with the 'Xtra Performance Technology' have a prolonged cooling zone at both lamp ends. The newly developed longmount cathode with extended protection ring ensures a more stable operation of the lamp over the entire lifetime. Available in the BodyTone and CLEO range.

XPT lamp characteristics

- Tanning:
 - enhanced tanning results through increased UVA
- Lamp operation:
 - more stable operation over total lifetime



PHILIPS BodyTone starter

BodyTone starters have been particularly developed for the use with tanning lamps tuned to the frequent on and off cycles. Go for safe and reliable ignition.

Click & Switch system

For easy installation place the new starter into the notches on top of the old starter body and

switch. Now, you can easily remove and replace the old against the new starter.

PHILIPS BodyTone starter characteristics

- More than 25% longer life span
- Minimum 6.000 cycles
- Eco-friendly and recyclable concept





BodyTone 30 <i>designed by Philips</i>	Lamp Wattage (W)	Reflec- tor o	UV- Code*	Dia- meter (mm)	Length (mm)	UVA (W)	UVA (W/m²)	UVB/ UVA (%)	Useful life (hrs.)	Ordering Code
BodyTone F21T5 25W / 30 EU1	25		25-O-10/3,1	16	520	11	7	0,9	500	996000141
BodyTone F71T12 100W-R / 30 EU1	100	o	100-R-22/2,2	38	1760	26	19	0,7	800	30021
BodyTone F71T12 100W-R / 30 EU3	100	o	100-R-27/2,7	38	1760	29	21	0,6	800	30011
BodyTone F79T12 120W-R / 30 EU1	120	o	120-R-19/2,0	38	2000	30	22	0,4	800	996000146
BodyTone F71T12 160W-R / 30 EU2	160	o	160-R-36/2,4	38	1760	36	23	0,8	800	996000152
BodyTone F71T12 160W-R / 30 EU 6	160	o	160-R-30/1,7	38	1760	44	25	0,5	800	30198
BodyTone DYX F71T12 160W-R / 30 EU1	80-200	o	160-R-24/2,0	38	1760	31	21	0,4	800	30041
BodyTone DYX F71T12 160W-R / 30 EU2	80-200	o	160-R-36/2,4	38	1760	38	23	0,8	800	996000150
BodyTone F79T12 180W-R / 30 EU1	180	o	180-R-36/2,6	38	2000	39	23	0,8	800	996000153

BodyTone 35 <i>designed by Philips</i>	Lamp Wattage (W)	Reflec- tor o	UV- Code	Dia- meter (mm)	Length (mm)	UVA (W)	UVA (W/m²)	UVB/ UVA (%)	Useful life (hrs.)	Ordering Code
BodyTone F59T12 80W-R / 35	80	o	80-R-27/2,4	38	1500	22	18	0,8	800	926548740
BodyTone F71T12 100W-R / 35	100	o	100-R-30/2,6	38	1760	27	19	0,9	800	926554840
BodyTone F59T12 140W-R / 35 XPT	140	o	140-R-31/2,9	38	1500	35	31	0,8	800	926565440
BodyTone F71T12 160W-R / 35	160	o	160-R-31/3,6	38	1760	38	22	0,6	800	926567840
BodyTone F71T12 160W-R / 35 XPT	160	o	160-R-35/3,3	38	1760	40	31	0,6	800	926569240
BodyTone F79T12 180W-R / 35 XPT	180	o	180-R-33/3,5	38	2000	45	28	0,6	800	926572240

BodyTone 45 <i>designed by Philips</i>	Lamp Wattage (W)	Reflec- tor o	UV- Code	Dia- meter (mm)	Length (mm)	UVA (W)	UVA (W/m²)	UVB/ UVA (%)	Useful life (hrs.)	Ordering Code
BodyTone F71T12 100W-R / 45	100	o	100-R-45/5,0	38	1760	26	18	1,3	800	926581440
BodyTone F71T12 160W-R / 45	160	o	160-R-49/3,0	38	1760	39	23	1,1	800	926585240
BodyTone F71T12 160W-R / 45 XPT	160	o	160-R-52/2,8	38	1760	44	31	1,0	800	926587640

* Example UV code on lamp: 160-R-31/2,9 160 = Wattage / R = Type of Reflector / 31 = X-Value / 2,9 = Y-Value

The respective data sheets of the lamps are available on request.



PHILIPS BodyTone Starter	Circuit	Mains voltage range (W)	Wattage range (W)	Packaging configuration	Ordering code
PHILIPS BodyTone Starter 15-20W	Single/Series	110-130 / 220-240	15-20	20 x 25	990334126
PHILIPS BodyTone Starter 25-100W	Single	220-240	25-100	20 x 25 / 1000	990370926 / 990370928
PHILIPS BodyTone Starter S12	Single	220-240	115-140	20 x 25 / 1000	990379226 / 990379228
PHILIPS BodyTone Starter 120-180W	Single	230-240	120-180	20 x 25 / 1000	990348826 / 990348828
PHILIPS BodyTone Starter electronic 15-180W	Single	200-260	15-180	20 x 25	990353226

CLEO by iSOLde

CLEO tanning lamps are characterised by their high efficiency as well as the stable output of every single lamp over the whole life span.

The results are high reliability and a compelling tanning effect.

The **CLEO by iSOLde** low pressure range is classified in five separate sections whilst complete product lines featuring all popular performances.

CLEO Advantage

CLEO Swift

CLEO Professional / -S

CLEO Performance / -S

CLEO Compact / -S



CLEO Advantage, CLEO Swift and

CLEO Professional-S provide very efficient, immediate and long-lasting pigmentation. A beautiful dark complexion can be obtained due to the high UV output.

These lamps are particularly designed for short tanning sessions. Cleo Swift feature noticeable higher UVA-output for immediate deep skin darkening.

CLEO Professional lamps are marked by their well balanced UVA UVB ratio. They afford excellent bio-positive parameters and therefore are ideally suitable for health care. (Vitamin D3 synthesis, compensation of sunlight deficiency).

CLEO Performance and CLEO Performance-S

help to achieve instant while gentle tanning effect. The lamps are ideal for people who enjoy extended tanning sessions. They also give long lasting tan to sensitive skin.



CLEO Compact und CLEO Compact S

are the product lines comprising short while extremely powerful tanning lamps. They are particularly designed for low pressure facial tanners.

CLEO HPA high pressure lamps

The Cleo by iSOLde high pressure range comprises lamps of high output and first

class performance. The Gold coating on either end guarantees ideal operating temperature within very short period.

CLEO HPA high pressure lamps are designed for use with Cleo and Body tone low pressure lamps. The range covers nearly the complete spectrum of performances and socket types affording high flexibility and attractive choice: All Cleo HPA high pressure lamps feature a life span of 800 hours.





CLEO Advantage designed by Philips	Lamp Wattage (W)	Reflec- tor °	UV- Code	Dia- meter (mm)	Length (mm)	UVA (W)	UVA (W/m²)	UVB/ UVA (%)	Useful life (hrs.)	Ordering code
CLEO Advantage F59T12 80W-R	80	°	80-R-81/9,2	38	1500	22	18	2,8	800	986619640
CLEO Advantage F71T12 100W	100		100-O-54/10,4	38	1760	30	11	3,2	800	986566340
CLEO Advantage F71T12 100W-R	100	°	100-R-90/9,6	38	1760	30	19	3,0	800	971036940
CLEO Advantage F79T12 100W-R	100	°	100-R-73/9,2	38	2000	31	17	2,8	800	996000121
CLEO Advantage F59T12 140W-R XPT	140	°	140-R-151/10,0	38	1500	34	30	3,3	800	926313140
CLEO Advantage F71T12 160W-R	160	°	160-R-138/10,3	38	1760	36	23	3,3	800	971038340
CLEO Advantage F71T12 160W-R XPT	160	°	160-R-151/10,0	38	1760	42	31	3,3	800	926295040
CLEO Advantage F75T12 180W-R	180	°	180-R-155/10,6	38	1900	23	23	3,3	800	30179
CLEO Advantage F79T12 180W-R	180	°	180-R-136/10,2	38	2000	40	23	3,2	800	996000200
CLEO Advantage F79T12 225W-R XPT	225 max	°	225-R-166/10,6	38	2000	56	33	3,4	800	995088840

CLEO Swift designed by Philips	Lamp Wattage (W)	Reflec- tor °	UV- Code	Dia- meter (mm)	Length (mm)	UVA (W)	UVA (W/m²)	UVB/ UVA (%)	Useful life (hrs.)	Ordering code
CLEO Swift F59T12 80W-R	80	°	80-R-57/5,4	38	1500	24	19	1,6	800	986571740
CLEO Swift F71T12 100W	100		100-O-36/6,2	38	1760	31	11	1,9	800	986728540
CLEO Swift F71T12 100W-R	100	°	100-R-61/5,5	38	1760	31	20	1,7	800	986617240
CLEO Swift F79T12 100W-R	100	°	100-R-48/5,7	38	2000	32	17	1,7	800	996000122
CLEO Swift F59T12 140W-R XPT	140	°	140-R-109/6,4	38	1500	39	31	2,0	800	926309440
CLEO Swift F71T12 160W-R	160	°	160-R-108/6,8	38	1760	44	24	2,1	800	986567040
CLEO Swift F71T12 160W-R XPT	160	°	160-R-112/6,4	38	1760	46	32	2,0	800	926266040
CLEO Swift F79T12 180W-R	180	°	180-R-111/7,4	38	2000	45	23	2,3	800	30482
CLEO Swift F79T12 200W-R XPT	200	°	200-R-119/6,4	38	2000	53	34	2,1	800	954135240
CLEO Swift F79T12 225W-R XPT	225	°	225-R-132/7,3	38	2000	59	34	2,2	800	995039040

CLEO Professional S designed by Philips	Lamp Wattage	Reflec- tor (W)	UV- Code °	Dia- meter	Length (mm) (mm)	UVA (W)	UVA (W/m²)	UVB/ UVA	Useful life (%)	Ordering code (hrs.)
CLEO Professional S F59T12 80W-R	80	°	80-R-47/5,7	38	1500	20	17	2,1	800	964165640
CLEO Professional S F71T12 100W	100		100-O-31/6,8	38	1760	27	10	2,4	800	964169440
CLEO Professional S F71T12 100W-R	100	°	100-R-50/6,0	38	1760	26	17	2,2	800	964171740
CLEO Professional S F59T12 140W-R	140	°	140-R-74/6,2	38	1500	32	21	2,3	800	964111340
CLEO Professional S F71T12 160W-R	160	°	160-R-75/6,2	38	1760	36	21	2,3	800	964113740

CLEO Professional designed by Philips	Lamp Wattage	Reflec- tor (W)	UV- Code °	Dia- meter	Length (mm) (mm)	UVA (W)	UVA (W/m²)	UVB/ UVA	Useful life (%)	Ordering code (hrs.)
CLEO Professional F59T12 80W-R	80	°	80-R-44/5,0	38	1500	20	17	1,3	800	962218140
CLEO Professional F71T12 100W	100		100-O-27/5,5	38	1760	27	10	1,5	800	962219840
CLEO Professional F71T12 100W-R	100	°	100-R-45/5,0	38	1760	26	18	1,3	800	962220440
CLEO Professional F59T12 140W-R	140	°	140-R-68/5,1	38	1500	32	21	1,5	800	962940140
CLEO Professional F71T12 160W-R	160	°	160-R-68/5,1	38	1760	37	22	1,5	800	962934040



CLEO Performance S <i>designed by Philips</i>	Lamp Wattage (W)	Reflec- tor o	UV- Code	Dia- meter (mm)	Length (mm)	UVA (W)	UVA (W/m²)	Useful life (hrs)	Ordering code
CLEO Performance S F59T12 80W	80		80-O-17/3,0	38	1500	20	10	800	964423740
CLEO Performance S F59T12 80W-R	80	o	80-R-27/2,4	38	1500	20	18	800	964425140
CLEO Performance S F71T12 100W	100		100-O-18/3,0	38	1760	27	10	800	964404640
CLEO Performance S F71T12 100W-R	100	o	100-R-30/2,6	38	1760	27	19	800	964406040

CLEO Performance <i>designed by Philips</i>	Lamp Wattage (W)	Reflec- tor o	UV- Code	Dia- meter (mm)	Length (mm)	UVA (W)	UVA (W/m²)	Useful life (hrs.)	Ordering code
CLEO Performance F24T12 40W	40		40-O-14/2,9	38	600	18	8	800	962830540
CLEO Performance F24T12 40W-R	40	o	40-R-25/2,5	38	600	18	16	800	962835040
CLEO Performance F59T12 80W	80		80-O-15/2,7	38	1500	20	10	800	962831240
CLEO Performance F59T12 80W-R	80	o	80-R-27/2,4	38	1500	20	18	800	962836740
CLEO Performance F71T12 100W	100		100-O-17/2,6	38	1760	27	10	800	962833640
CLEO Performance F71T12 100W-R	100	o	100-R-29/2,4	38	1760	27	19	800	962838140
CLEO Performance F71T12 160W-R	160	o	160-R-49/3,0	38	1760	39	23	800	963641640

CLEO Compact S <i>designed by Philips</i>	Lamp Wattage (W)	Reflec- tor o	UV- Code	Dia- meter (mm)	Length (mm)	UVA (W/m²)	UVB/ UVA (%)	Useful life (hrs.)	Ordering code
CLEO Compact S 25W	25		25-O-23/6,5	16	520	6	2,5	500	962979127
CLEO Compact S 25W-R	25	o	25-R-48/6,8	16	520	11	2,1	500	963369927

CLEO Compact <i>designed by Philips</i>	Lamp Wattage (W)	Reflec- tor o	UV- Code	Dia- meter (mm)	Length (mm)	UVA (W/m²)	UVB/ UVA (%)	Useful life (hrs.)	Ordering code
CLEO Compact 15W	15		15-O-9/3,9	16	288	4	1,3	500	971646027
CLEO Compact 20W	20		20-O-14/3,9	28	438	6	1,4	500	961205240
CLEO Compact 25W	25		25-O-14/3,5	16	520	6	1,3	500	961911227
CLEO Compact PLL 36W	36		36-O-33/4,6	18	415	16	1,1	500	995325440



CLEO HPA designed by Philips	Lamp Wattage (W)	Main voltage (V)	Cap/Base	UVA (W) (Radiation 1 hr. IEC)	Length (mm)	Useful life (hrs.)	Ordering code
CLEO HPA Synergy 300W	300	230	R75 (clip-in) / R75	64	104	800	920650329
CLEO HPA 400 SE	400	230	Single Ended / GY 9.5	82	113	800	919822845
CLEO HPA 400 S	400	230	R75 (clip-in) / R75	87	118	800	919220245
CLEO HPA 400/30 S	400	230	R75 (clip-in) / R75	94	104	800	919159545
CLEO HPA 400/30 S L	400	230	R75 (clip-in) / R75	94	106	800	913138841
CLEO HPA 400/30 SD	400	230	R75 (clip-in) / R75	94	104	800	919165645
CLEO HPA 400/30 SD L	400	230	R75 (clip-in) / R75	94	106	800	913137141
CLEO HPA 400/30 SDC	400	230	Cable / Ferrule	94	96 + 2	800	919300145
CLEO HPA 250-500 SE	250 / 500	230	Single Ended / GY 9.5	42 / 123	113	800	913134045
CLEO HPA 250-500/30 SD	250 / 500	230	R75 (clip-in) / R75	51 / 125	104	800	920184345
CLEO HPA 250-500/30 FX L	250 / 500	230	R75 (clip-in) / R75	51 / 125	106	800	913132641
CLEO HPA Flexpower 400-600W	400 / 600	230	R75 (clip-in) / R75	87	118	800	919798629
CLEO HPA 610 FX	600	230	Contact plate 600	141	141 ± 1	800	921378541
CLEO HPA 620 FX	600	230	Cable / Cover	141	158 ± 1,5	800	921376145
CLEO HPA 630 FX	600	230	Contact pin 600	141	141 ± 1	800	921380841
CLEO HPA 640 SE FX	400 / 600	230	Single Ended / GY 9.5	94 / 141	113; from cap max 109	800	914211755

CLEO HPA High Wattage designed by Philips	Lamp Wattage (W)	Main Voltage (V)	Cap/Base	UVA (W) (Radiation 1 hr. IEC)	Length (mm)	Useful life (hrs.)	Ordering code
CLEO HPA 700 S FX	700	230	R75 (clip-in) / R75	187	117,9	800	920669541
CLEO HPA 700/800 FX C	700	230	Cable / Cover	187	126,5 ± 2	800	920674931
CLEO HPA 1000 SE	1000	230	Single Ended / Cap GQ 9.5	245	138 (max)	800	919930075
CLEO HPA 1000 SE FX	1000	230	Single Ended / GQ 9.5	245	138 (max)	800	913129645
CLEO HPA 1000 S	1000	230	Cable / Ferrule	243	147 ± 2	800	919109045
CLEO HPA 1000 FX	1000	230	Cable / C14X Ferrule	243	147 ± 2	800	938666545
CLEO HPA 1010 SE FX	1000	230	Single Ended / Cap GQ 9.5	245	109,5 (max)	800	938670245
CLEO HPA 1040 SE FX	1000	230	Single Ended Key / GA 9.5	245	124 (max)	800	913128945
CLEO HPA 1200 S	1200	230	Cable / Cover	308	139 ± 2	800	919130445
CLEO HPA 1200 S FX	1200	230	Cable / C10.5 S Cover	308	139 ± 2	800	938668945
CLEO HPA 1200 FX	1200	400	Cable / C10.5 L Cover	308	166 ± 2	800	913103645
CLEO HPA 1220 FX	1200	400	Cable / Cover	317	137 ± 3	800	913133345
CLEO HPA 2000 S	2000	400	Cable / C14X Ferrule	550	177 ± 2	800	919127445
CLEO HPA 2000 S FX	2000	400	Cable / C14X Ferrule	550	177 ± 2	800	938667245
CLEO HPA 2020 S	2000	400	Cable / C10.5 L Cover	537	185 ± 3	800	919535745
CLEO HPA 2020 S FX	2000	400	Cable / C10.5 L Cover	537	185 ± 3	800	938665845
CLEO HPA 2040 S FX	2000	230	Cable / C10.5 L Cover	576	171 ± 3	800	920671845

iSOLde

Professional tanning lamps

iSOLde is an exclusive tanning lamps brand *designed by Philips*.

iSOLde has taken over the renowned Philips tanning range at the beginning of the year 2009 and ever since is leading the 25-year long success story into a bright future.

JW Sales GmbH
Brand Division iSOLde
Kölner Straße 8
D-70376 Stuttgart
Phone +49 (0)711 / 54 00 4-0
Fax +49 (0)711 / 54 00 4-55
info@isoldelicht.de
www.isoldelicht.de

PHILIPS

Exclusive distributor
of Philips tanning lamps

Warning: DANGER - Ultraviolet radiation. Important instructions. Avoid overexposure. As with natural sunlight, overexposure can cause eye and skin injury and allergic reactions. Repeated exposure may cause premature aging of the skin and skin cancer. WEAR PROTECTIVE EYEWEAR; FAILURE TO MAY RESULT IN SEVERE BURNS OR LONG-TERM INJURY TO THE EYES. Medications or cosmetics may increase your sensitivity to the ultraviolet radiation. Consult physician before using sunlamp if you use medications or have a history of skin problems or believe yourself to be especially sensitive to sunlight. If you do not tan in the sun, you are unlikely to tan from the use of this product.

All rights reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice. No liability will be accepted by the publisher for any consequence of its use. Publication thereof does not convey nor imply any license under patent- or other industrial or intellectual property rights.